

Material Designation: PC8020

Product Description: Polycarbonate (PC), "STAR PRIME", furnished as pellets

Color	Min. Thk (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str
ALL	1.5	V-0	-	-	80	80	80
	3.0	V-0	-	-	80	80	80

Comparative Tracking Index (CTI): -

Inclined Plane Tracking (IPT): -

Dielectric Strength (kV/mm): -

Volume Resistivity (10^x ohm-cm): -

High-Voltage Arc Tracking Rate (HVTR): -

High Volt, Low Current Arc Resis (D495): -

Dimensional Stability (%): -

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliance, where the acceptability of the combination is determined by UL.

Report Date: 2014-02-11

Last Revised: 2014-02-10

2013 UL LLC©

**IEC and ISO Test Methods**

Test Name	Test Method	Units	Thickness Tested (mm)		Value
			1.5	3.0	
Flammability	IEC 60695-11-10	Class (color)	1.5		V-0 (ALL)
				3.0	V-0 (ALL)
Glow-Wire Flammability (GWFI)	IEC 60695-2-12	C	-		-
Glow-Wire Ignition (GWI)	IEC 60695-2-13	C	-		-
IEC Comparative Tracking Index	IEC 60112	Volts (Max)	-		-
IEC Ball Pressure	IEC 60695-10-2	C	-		-
ISO Heat Deflection (1.80 MPa)	ISO 75-2	C	-		-
ISO Tensile Strength	ISO 527-2	MPa	-		-
ISO Flexural Strength	ISO 178	MPa	-		-
ISO Tensile Impact	ISO 8256	kJ/m ²	-		-
ISO Izod Impact	ISO 180	kJ/m ²	-		-
ISO Charpy Impact	ISO 179-2	kJ/m ²	-		-

Your Competitive Advantage in an Ever Changing Market!